

DATE CREATED: 01 / 01 / 2025

# FOIL SCRIM KRAFT ALUMINUM FOIL TAPE - IS 56214 V

120 MICRON

## **PRODUCT DESCRIPTION**

IS 56214 V FSK (Foil Scrim Kraft) Tape is a premium laminated tape reinforced with glass fibers, providing exceptional strength and puncture resistance. This tape is specifically designed for sealing seams and joints of fiberglass and aluminum backed duct boards, offering a superior vapor barrier and the ability to conform to irregular surfaces. Additionally, FSK aluminum foil tape is ideal for shielding and covering thermal insulation.

## **PRODUCT STRUCTURE**



# **PRODUCT FEATURE**

- Conformability: Easily conforms to irregular surfaces, ensuring a secure seal.
- Cost-Efficient: Offers a low-cost solution with high efficiency for HVAC applications.
- Mold Resistant: Designed to resist mold growth, promoting a healthier environment.
- Reinforced Strength: Laminated with glass fibers for added durability and puncture resistance.
- Excellent Vapor Barrier: Provides a robust barrier to vapor, enhancing insulation effectiveness.

#### PRODUCT APPLICATION

- HVAC Solutions: Cost-effective and highly efficient for various HVAC applications.
- Vapor Sealing: High-performance insulation tape ideal for vapor sealing applications.
- Inconspicuous Repairs: Excellent for making discreet repairs to foil-backed insulation.
- Duct Insulation Sealing: Perfect for sealing rigid and blanket-style fiberglass duct insulation.
- Thermal Insulation Reinforcement: Suitable for reinforced fiberglass and mineral-wool thermal insulation

#### **PHYSICAL PROPERTIES**

CHARACTERISTIC	UNIT	VALUE
COLOR	-	Silver
BACKING	-	Aluminum Foil
ADHESIVE TYPE	-	Hotmelt Based
THICKNESS	MIC	120 ± 0.05
INITIAL TACK	STEEL BALL NO.	# 10
TENSILE STRENGTH	N/25MM	≥ 75
HOLDING POWER	Н	≥ 12
PEEL ADHESION	N/25MM	≥ 18
ELONGATION	%	≥ 0
TEMPRATURE RESISTANT	°C	-40 – 120

Information in the above sheet is the average value of the tests, it should not be taken as the exact values of every single product. Customers have the obligation to check whether the product is suitable for their own applications.

#### STORAGE AND USAGE

Tape should be stored in dry, cool, shelter area and avoid direct sunlight, storage temperature under 40°C under correct storage conditions maintains its characteristics for two years.

# **NOTICE**

- Please try a sample and make sure the tape is suitable for the application before use it.
- Customers who buy the jumbo rolls should stop the re-winding and slitting once find that there has quality problem with the jumbo. Contact us right away. If customers re-wind/cut the problematic jumbo into log/finished rolls, Instabiz Solutions India Pvt. Ltd. will not response to make any indemnity.
- Ideal tape application temperature is 8 to 38 Celsius. It is not suggested to use the tape below zero Celsius, because the adhesive will become too firm to adhere readily. However, once customers insist on using the tape under such a low temperature, please contact us, Instabiz Solutions India Pvt. Ltd. will adjust the adhesive, but Instabiz Solutions India Pvt. Ltd. doesn't guarantee anything.
- Firm application pressure helps develop better adhesive contact and improves bond strength, the bonding surfaces must be clean, dry and well unified. Seal completely when not use the tape, avoid expose the tape in the sunlight.
- Expiry date: Original packaging, 23 C & 60% humidity, 12 months after production date. If product is not kept under such temperature and humidity, jumbo/log rolls should be finished within four months, finished rolls should be finished within one month.
- All Instabiz Solutions India Pvt. Ltd. products are strict inspected before sent to customers, but the applications might be different between different customers, there may exist factors which are
  beyond Instabiz Solutions India Pvt. Ltd. knowledge and control, so customers should check the quality of every order before use the tape. If customers use the product without inspection, they
  must be responsible for the potential quality problems and economic loss. If the product is proved to be defective, the exclusive remedy, at Instabiz Solutions India Pvt. Ltd. option, shall be to
  refund the purchase price of or replace the problematic product.